

## Seal Food Merchandiser (650 Refrigerated – Rectangular)

### Key Features

- Type: Refrigerated counter-top unit
- Top-mounted power pack for all round visibility
- R404a refrigerant
- Thermostatic temperature control with digital display
- Cabinet temperature 3°-5°C
- Fan cooled condenser
- Automatic defrost and condensate water evaporation
- Blown air circulation
- Diffused internal light
- Adjustable shelf positions
- Supplied with two chrome plated shelves
- Meets the performance requirements of BS EN ISO 23953-2:2005 Climate Class 3M2



D6R/100R

### Construction

- Body: powder coated aluminium frame (silver)
- Internal components: stainless steel grade 430
- Glazing: toughened safety glass, double glazed
- Door: sliding rear doors
- Panel: black plastic coated steel
- Base plinth: black plastic coated steel
- Shelves: chrome plated

### Available Options


- Choice of three widths
- Choice of self service or back service
- 60Hz supply (price on request)

### Available Accessories

N/A

## Specifications

Model	D6R/75B	D6R/75S	D6R/100B	D6R/100S	D6R/125B	D6R/125S
External height (mm)	965					
External width (mm)	750		1000		1250	
External depth (mm)	650					
Capacity net volume (litres)	221		300		380	
Back or Self-service	Back	Self-Service	Back	Self-Service	Back	Self-Service
Number of Shelves (including base)	3					
Shelf dimensions W x D (mm)	650 x 525		900 x 525		1150x 525	
Cabinet temperature ( °C)	3°C -5°C					
Food holding temperature(°C)	-1°C -7°C					
Maximum ambient temperature ( °C)	25°C					
Maximum ambient relative humidity (%)	60%					
Total power rating kW	0.602		0.717		0.729	
Electrical supply 1N~+E 230V 50-60Hz Current Rating (A)	3		4			
Net weight unpacked (kg)	95		123		150	149
Gross weight packed (kg)	127		155		178	
Shipping volume (m <sup>3</sup> )	0.789		1.022		1.211	



Lincat Limited, Whisby Road,  
Lincoln LN6 3QZ,  
United Kingdom

UK Sales Tel: 01522 875500 UK Spares Tel: 01522 875510 UK General Tel: 01522 875555  
 UK Fax: 01522 875530 International Sales Tel: +44 1522 503250 International Fax: +44 1522 875530  
 Website: www.lincat.co.uk UK Sales e-mail: sales@lincat.co.uk International Sales e-mail: export@lincat.co.uk



Document ref:  
SEAL650REFRECT  
Issue date: Dec-09